

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International publication date
29 July 2004 (29.07.2004)

PCT

(10) International publication number
WO 2004/062498 A1

(51) International patent classification⁷:
A61B 5/055, A61K 49/06, G01R 33/28, 33/485

(21) International application number:
PCT/FR2003/003628

(22) International filing date:
8 December 2003 (08.12.2003)

(25) Language of filing: French

(26) Language of publication: French

(30) Data relating to the priority:
02/15,826 13 December 2002 (13.12.2002) FR

(71) Applicants (for all designated States except US):
CENTRE NATIONAL DE LA RECHERCHE
SCIENTIFIQUE - CNRS [FR/FR]; 3, rue Michel Ange,
F-75794 Paris Cedex 16 (FR). UNIVERSITE VICTOR
SEGALEN BORDEAUX 2 [FR/FR]; 146, rue Léo-
Saignat, F-33076 Bordeaux Cedex (FR).

(72) Inventors; and


(75) Inventors/Applicants (US only): FRANCONI, Jean-
Michel [FR/FR]; 27 rue Charles Boubes, F-33700
Mérignac (FR). MIRAUX, Sylvain [FR/FR]; 14 rue
Riaud, F-33700 Merignac (FR). THIAUDIERE, Eric
[FR/FR]; 31 rue Grandier-Vazeille, F-33000 Bordeaux
(FR). CANIONI, Paul [FR/FR]; 18 avenue Maurice
Faye, F-33600 Pessac (FR).

[continued on next page]

As printed

(54) Title: METHOD FOR ACQUIRING ELECTROMAGNETIC SIGNALS AND CONTRAST PRODUCT THEREFOR

(54) Titre : PROCEDE D'ACQUISITION DE SIGNAUX ELECTROMAGNETIQUES ET PRODUIT DE CONTRASTE POUR UNE TELLE ACQUISITION



WO 2004/062498 A1

(57) Abstract: The invention concerns a system capable of generating a magnetic induction B_0 comprising gradients (G_x, G_y, G_z) in certain directions, transmitting radio frequency wave pulse sequences (RF) perpendicular to B_0 in a range of adjustable frequencies, and detecting electromagnetic signals received from a body part (4). The method consists in: injecting a contrast product in said body part, capable of being temporarily fixed in an observed zone (1), and comprising an element capable of causing chemical displacement of a resonance frequency of water hydrogen protons; exciting said body part, using a radio frequency wave pulse sequence in a range of frequencies adjusted on the basis of the magnetic induction B_0 and the chemical displacement for some of said waves; detecting the electromagnetic signals received in said body part, substantially corresponding to the magnetic resonance signals of the protons of the observed zone having undergone the chemical displacement.

(57) Abrégé: Un système peut générer une induction magnétique B_0 comprenant des gradients (G_x, G_y, G_z) dans certaines directions, émettre des séquences d'impulsions d'ondes de radiofréquence (RF) perpendiculaires à B_0 dans une gamme de fréquences réglables, et détecter des signaux électromagnétiques reçus depuis une portion

[continued on next page]